

Министерство строительства и жилищно-
коммунального хозяйства Республики Узбекистан
Архитектурно-проектная группа
общество с ограниченной ответственностью

ООО "SILVER RAIN PROJECT"

Лицензия Госкомархстрой № АЛ-000224 от 19.09.2019г.

Объект: "Зангиота тумани "Далигузар" МФЙ худудидаги
15-сонли ДМТТ ёиносини реконструкция килиш"

АС - Архитектурные строительные решения

"Площадка для мусорного
контейнера"

Директор:



Халилов Н.

Главный архитектор проекта:



Кувондилов А

Главный инженер проекта:



Жабборов О

Ташкент-2026г

Technical drawing of a wall section. The wall is represented by a brick pattern. There are two rectangular openings in the wall. A vertical dimension line on the left indicates a height of 1260.

Technical drawing of a building facade showing a brick wall with windows and doors. The drawing includes dimensions in millimeters (mm) for the overall structure and individual components.

Vertical Dimensions (mm):

- Overall height: 1190
- Height of the main brick wall section: 270
- Height of the lower section (including the base): 140
- Height of the base: 210
- Height of the base (alternative measurement): 140

Horizontal Dimensions (mm):

- Overall width: 1000
- Width of the main brick wall section: 450
- Width of the base: 250
- Width of the base (alternative measurement): 120
- Width of the base (alternative measurement): 120
- Width of the base (alternative measurement): 120
- Width of the base (alternative measurement): 250
- Width of the base (alternative measurement): 100

Architectural cross-section drawing of a building's foundation and ground floor. The drawing shows a concrete slab (Бетон кл.В15) with a gravel preparation (Гравийная подготовка) underneath. The slab is supported by a foundation. The drawing includes dimensions for the slab thickness (1190 mm), the gravel preparation (100 mm), and the foundation (300 mm). It also shows the ground level (+1.170) and the foundation level (-0.490). The drawing is labeled "Разрез 1 - 1" and "Слив С-1".

Technical drawing of a waste container (мусорный контейнер) showing top and side views with dimensions in millimeters.

Top View Dimensions:

- Overall width: 3500
- Overall height: 1110
- Internal width (between compartments): 3000
- Internal height (between compartments): 1360
- Side panel thickness: 250
- Top panel thickness: 125
- Bottom panel thickness: 450

Side View Dimensions:

- Overall width: 3500
- Overall height: 1110
- Internal width (between compartments): 3000
- Internal height (between compartments): 1360
- Side panel thickness: 250
- Top panel thickness: 125
- Bottom panel thickness: 450

Labels:

- Мусорный контейнер (Waste container)
- 1 (Scale indicator)

Дмб. 120x70(н)
отм. нуля -0.02

Поз.	Обозначение	Наименование	Кол-во, шт	Примеч.
		<u>Фундамент</u>		
	<u>Материалы</u>	Бетон кл.В15	1	1,4 м3
		Гравийная подготовка	1	0,66 м3
		Кирп. М50 кладка на раств. М25	1	1,8 м3
С-1	ГОСТ 17715-72	Оцинк.кров. сталь t=0,5		2,3 м2

1. В основании фундамента выполнить подготовку из гравия фракции 20–40 мм. толщ. 100 мм. с проливкой горячим битумом до полного насыщения и образования сверху пленки толщ. 4–5 мм.
2. Боковые поверхности фундамента, соприкасающиеся с грунтом покрыть битумной мастикой (ГОСТ 2889–80) в 2 слоя по грунтовке.
3. Горизонтальная гидроизоляция на отм. –0.030 2 слоя рубероида на битумной мастике 1,7 м².
4. Ограждающая стенка из кирпича М50 на растворе М25, кладка под расшивку швов
5. При кладке стенки предусмотреть отверстия

AC

Изм.	Кол.уч.	Лист	№дог.	Подпись	Дата
ГИП		Жаёдорав О			
ГАП		Кувондииков А			
Разраб		Жаёдорав О			
Н. Контрол		Халилов Н.			

	Стадия	Лист	Листов
"Архитектурные строительные решения"	РП	1	1

000 "SILVER RAIN PROJECT"
Ташкент-2026г