

Technical drawing of a rectangular foundation pit. The drawing shows a cross-section of the pit with dimensions and labels.

Dimensions:

- Overall width: 6600 mm
- Overall height: 5600 mm
- Inner width: 6000 mm
- Inner height: 5000 mm
- Thickness of the pit walls: 200 mm
- Thickness of the pit floor: 100 mm
- Thickness of the pit walls (inner): 500 mm
- Thickness of the pit floor (inner): 1500 mm

Labels:

- Армированная бетонная площадка 6400x5400x200 мм (Reinforced concrete platform 6400x5400x200 mm)
- Гравийная подготовка 6600x5600x100 мм (Gravel preparation 6600x5600x100 mm)
- Длина 6000 мм. Ширина 5000 мм. Высота 3000 мм. (Length 6000 mm. Width 5000 mm. Height 3000 mm.)

Выемка грунта - 175,38 м³;

Technical drawing of a building section showing a cross-section with a central rectangular room and sloped roof sections. The drawing includes dimensions for height (3000, 2700), width (1500, 500, 6400, 500, 1500), and total width (10400). Elevation markers are shown at ± 0.000 , $+0.100$, and $+3.000$. A dashed line indicates a lower level within the central room.

Марка	Обозначение	Наименование	Кол- тво	Масса ед. кг	примеча- ние
		Гравийная подготовка 6600х5600х100мм			3,69 м ³
		Армированная бетонная площадка 10800х6200х200мм			
		Сетка ячейкой 200х200мм			
1	ГОСТ 7348-81*	Сетка С $\phi 10 \text{ AIII}-200$ $\phi 10 \text{ AII}-200$ S=34,56 м ²	1	на 1м ² 7,40кг.	255,74 кг
	Материал	Бетон кл.В 12.5 (Обще)			6,91 м ³

[illegible]